

SAFETY DATA SHEET

according to Regulation (EC) No 1907/2006 (REACH) as amended



Sample Logo

EXAMPLE Dangerous mixture

Creation date 10th December 2019
Revision date Version 1.0

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- 1.1. Product identifier**
Substance / mixture EXAMPLE Dangerous mixture
UFI mixture P300-A06R-300M-GH76
- 1.2. Relevant identified uses of the substance or mixture and uses advised against**
Mixture's intended use Degreasing agent.
Mixture uses advised against The product should not be used in ways other than those referred in Section 1.
EuPCS PC-CLN-2
- 1.3. Details of the supplier of the safety data sheet**
Manufacturer
Name or trade name SBLCore s.r.o.
Address Sezemická 2757/2, Praha 9 - Horní Počernice, 193 00
Czech Republic
Identification number (CRN) 04278968
VAT Reg No CZ04278968
Phone +420 725 582 495
E-mail sblcore@sblcore.com
Web address www.sblcore.com
- Competent person responsible for the safety data sheet**
Name SBLCore s.r.o.
E-mail sblcore@sblcore.com
- 1.4. Emergency telephone number**
National Health Service (NHS) 111

SECTION 2: Hazards identification

- 2.1. Classification of the substance or mixture**
Classification of the mixture in accordance with Regulation (EC) No 1272/2008
The mixture is classified as dangerous.

Flam. Liq. 2, H225
Asp. Tox. 1, H304
Skin Irrit. 2, H315
Skin Sens. 1, H317
Eye Irrit. 2, H319
STOT SE 3, H336
STOT RE 2, H373 (hearing organs, kidneys)
Aquatic Chronic 2, H411

Full text of all classifications and hazard statements is given in the section 16.

Most serious adverse physico-chemical effects

Highly flammable liquid and vapour.

Most serious adverse effects on human health and the environment

May be fatal if swallowed and enters airways. May cause damage to hearing organs, the kidneys through prolonged or repeated exposure. Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation. May cause drowsiness or dizziness. Toxic to aquatic life with long lasting effects.

- 2.2. Label elements**
Hazard pictogram



Signal word

Danger

SAFETY DATA SHEET

according to Regulation (EC) No 1907/2006 (REACH) as amended



Sample Logo

EXAMPLE Dangerous mixture

Creation date 10th December 2019
Revision date Version 1.0

Hazardous substances

cyclohexane
fenoxaprop-P-ethyl (ISO)
isopropanol

Hazard statements

H225 Highly flammable liquid and vapour.
H304 May be fatal if swallowed and enters airways.
H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H319 Causes serious eye irritation.
H336 May cause drowsiness or dizziness.
H373 May cause damage to hearing organs, the kidneys through prolonged or repeated exposure.
H411 Toxic to aquatic life with long lasting effects.

Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P280 Wear protective gloves.
P301+P310 IF SWALLOWED: Immediately call a doctor.
P331 Do NOT induce vomiting.
P370+P378 In case of fire: Use powder extinguisher/sand/carbon dioxide to extinguish.
P391 Collect spillage.

2.3. Other hazards

Mixture does not contain any substance meet the criteria for PBT or vPvB in accordance with Annex XIII of Regulation (EC) No. 1907/2006 (REACH) as amended.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Chemical characterization

Mixture of substances and additives specified below.

Mixture contains these hazardous substances and substances with the highest permissible concentration in the working environment

Identification numbers	Substance name	Content in % weight	Classification according to Regulation (EC) No 1272/2008	Note.
Index: 601-023-00-4 CAS: 100-41-4 EC: 202-849-4 Registration number: 01-2119489370-35	ethylbenzene	20	Flam. Liq. 2, H225 Asp. Tox. 1, H304 Acute Tox. 4, H332 STOT RE 2, H373 (hearing organs)	1
Index: 601-017-00-1 CAS: 110-82-7 EC: 203-806-2 Registration number: 01-2119463273-41	cyclohexane	10-15	Flam. Liq. 2, H225 Asp. Tox. 1, H304 Skin Irrit. 2, H315 STOT SE 3, H336 Aquatic Acute 1, H400, M=1 Aquatic Chronic 1, H410, M=1	1, 2
Index: 607-707-00-9 CAS: 71283-80-2 Registration number: 01-3179417542-24	fenoxaprop-P-ethyl (ISO)	10	Skin Sens. 1, H317 STOT RE 2, H373 (kidneys) Aquatic Acute 1, H400, M=1 Aquatic Chronic 1, H410, M=1	
Index: 603-117-00-0 CAS: 67-63-0 EC: 200-661-7 Registration number: 01-2119457558-25	isopropanol	9	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336	1
Index: 603-002-00-5 CAS: 64-17-5 EC: 200-578-6 Registration number: 01-2119457610-43	ALCOHOL	5	Flam. Liq. 2, H225 Specific concentration limit: Eye Irrit. 2, H319: C ≥ 50 %	1

SAFETY DATA SHEET

according to Regulation (EC) No 1907/2006 (REACH) as amended



Sample Logo

EXAMPLE Dangerous mixture

Creation date	10th December 2019	Version	1.0
Revision date			

Notes

- 1 Substance for which exposure limits of Community for working environment exist.
- 2 The use of the substance is restricted by Annex XVII of REACH Regulation

Full text of all classifications and hazard statements is given in the section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

Take care of your own safety. If any health problems are manifested or if in doubt, inform a doctor and show him information from this safety data sheet. If unconscious, put the person in the stabilized (recovery) position on his side with his head slightly bent backwards and make sure that airways are free; never induce vomiting. If the person vomits by himself, make sure that the vomit is not inhaled. In life threatening conditions first of all provide resuscitation of the affected person and ensure medical assistance. Respiratory arrest - provide artificial respiration immediately. Cardiac arrest - provide indirect cardiac massage immediately.

If inhaled

Take care of your own safety, do not let the affected person walk! Terminate the exposure immediately; move the affected person to fresh air. Beware of the contaminated clothes. Depending on the situation, call the medical rescue service and ensure medical treatment considering the frequent need of further observation for at least 24 hours.

If on skin

Remove contaminated clothes. Wash the affected area with plenty of water, lukewarm if possible. Soap, soap solution or shampoo should be used if there is no skin injury. Provide medical treatment if skin irritation persists. Rinse skin with water/shower.

If in eyes

Rinse eyes immediately with a flow of running water, open the eyelids (also using force if needed); remove contact lenses immediately if worn by the affected person. Rinsing should continue at least for 10 minutes. Provide medical treatment, specialized if possible.

If swallowed

If the affected person vomits, make sure to prevent inhalation of the vomit (as there is a danger of lung damage after inhalation of these liquids in the airways also in infinitesimal amount). Provide medical treatment considering the frequent need of further observation for at least 24 hours. Bring an original container with the label and the Safety Data Sheet of the given substance as appropriate.

4.2. Most important symptoms and effects, both acute and delayed

If inhaled

Cough, headache. May cause drowsiness or dizziness.

If on skin

May cause an allergic skin reaction.

If in eyes

Causes serious eye irritation.

If swallowed

Irritation, nausea.

4.3. Indication of any immediate medical attention and special treatment needed

Symptomatic treatment.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Alcohol-resistant foam, carbon dioxide, powder, water spray jet, water mist.

Unsuitable extinguishing media

Water - full jet.

5.2. Special hazards arising from the substance or mixture

In the event of fire, carbon monoxide, carbon dioxide and other toxic gases may arise. Inhalation of hazardous degradation (pyrolysis) products may cause serious health damage.

5.3. Advice for firefighters

Self-Contained Breathing Apparatus (SCBA) with a chemical protection suit only where personal (close) contact is likely. Use a self-contained breathing apparatus and full-body protective clothing. Closed containers with the product near the fire should be cooled with water. Do not allow run-off of contaminated fire extinguishing material to enter drains or surface and ground water.

SAFETY DATA SHEET

according to Regulation (EC) No 1907/2006 (REACH) as amended



Sample Logo

EXAMPLE Dangerous mixture

Creation date 10th December 2019
Revision date Version 1.0

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Provide sufficient ventilation. Highly flammable liquid and vapour. Remove all ignition sources. Use personal protective equipment for work. Follow the instructions in the Sections 7 and 8. Do not inhale aerosols. Prevent contact with skin and eyes.

6.2. Environmental precautions

Do not allow to enter drains. Prevent contamination of the soil and entering surface or ground water.

6.3. Methods and material for containment and cleaning up

Spilled product should be covered with suitable (non-flammable) absorbing material (sand, diatomaceous earth, earth and other suitable absorption materials); to be contained in well closed containers and removed as per the Section 13. In the event of leakage of the substantial amount of the product, inform fire brigade and other competent bodies. After removal of the product, wash the contaminated site with plenty of water. Do not use solvents.

6.4. Reference to other sections

See the Section 7, 8 and 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Prevent formation of gases and vapours in flammable or explosive concentrations. The product should be used only in the areas where it is not in contact with open fire and other ignition sources. Use non-sparking tools. Use of antistatic clothes and footwear is recommended. Do not inhale aerosols. Prevent contact with skin and eyes. No smoking. Use only non-sparking tools. Contaminated work clothing should not be allowed out of the workplace. Wash hands and exposed parts of the body thoroughly after handling. Use only outdoors or in a well-ventilated area. Use personal protective equipment as per Section 8. Observe valid legal regulations on safety and health protection. Ground and bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting equipment. Take precautionary measures against static discharge. Avoid release to the environment.

7.2. Conditions for safe storage, including any incompatibilities

Store in tightly closed containers in cold, dry and well ventilated areas designated for this purpose. Do not expose to sunlight. Store locked up. Keep container tightly closed. Keep cool.

Content

435 ml

Material of package

ALU (41), Aluminium (Metals)



ALU

The specific requirements or rules relating to the substance/mixture

Solvent vapours are heavier than air and accumulate especially near the floor where they may form an explosive mixture with the air.

7.3. Specific end use(s)

not available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

European Union

Substance name (component)	Type	Time of exposure	Value	Note	Source
ethylbenzene (CAS: 100-41-4)	OEL	8 hours	442 mg/m ³	Skin	Commission Directive 2000/39/EC
	OEL	8 hours	100 ppm	Skin	
	OEL	15 minutes	884 mg/m ³	Skin	

SAFETY DATA SHEET

according to Regulation (EC) No 1907/2006 (REACH) as amended



Sample Logo

EXAMPLE Dangerous mixture

Creation date 10th December 2019
Revision date Version 1.0

European Union

Substance name (component)	Type	Time of exposure	Value	Note	Source
ethylbenzene (CAS: 100-41-4)	OEL	15 minutes	200 ppm	Skin	Commission Directive 2000/39/EC
cyclohexane (CAS: 110-82-7)	OEL	8 hours	700 mg/m ³		Commission Directive 2006/15/EC
	OEL	8 hours	200 ppm		

United Kingdom of Great Britain and Northern Ireland

Substance name (component)	Type	Time of exposure	Value	Note	Source
ethylbenzene (CAS: 100-41-4)	WEL	8 hours	441 mg/m ³		GBR
	WEL	Short-term	552 mg/m ³		
	WEL	8 hours	100 ppm		
	WEL	Short-term	125 ppm		
cyclohexane (CAS: 110-82-7)	WEL	8 hours	350 mg/m ³		GBR
	WEL	1 hour	1050 mg/m ³		
	WEL	8 hours	100 ppm		
	WEL	1 hour	300 ppm		
isopropanol (CAS: 67-63-0)	WEL	8 hours	999 mg/m ³		GBR
	WEL	1 hour	1250 mg/m ³		
	WEL	8 hours	400 ppm		
	WEL	1 hour	500 ppm		
ALCOHOL (CAS: 64-17-5)	WEL	8 hours	1920 mg/m ³		GBR
	WEL	8 hours	1000 ppm		

8.2. Exposure controls

Follow the usual measures intended for health protection at work and especially for good ventilation. This can be achieved only by local suction or efficient general ventilation. If exposure limits cannot be observed in this mode, suitable protection of airways must be used. Do not eat, drink and smoke during work. Wash your hands thoroughly with water and soap after work and before breaks for a meal and rest.

Eye/face protection

Protective goggles.

Skin protection

Hand protection: Protective gloves resistant to the product. When choosing appropriate thickness, material and permeability of the gloves, observe recommendations of their particular manufacturer. Observe other recommendations of the manufacturer. Other protection: protective workwear. Contaminated skin should be washed thoroughly.

Respiratory protection

Mask with a filter against organic vapours in a poorly ventilated environment.

Thermal hazard

Not available.

Environmental exposure controls

Observe usual measures for protection of the environment, see Section 6.2. Collect spillage.

SAFETY DATA SHEET

according to Regulation (EC) No 1907/2006 (REACH) as amended



Sample Logo

EXAMPLE Dangerous mixture

Creation date	10th December 2019	Version	1.0
Revision date			

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance	
Physical state	liquid at 20°C
color	colourless
Odour	after solvents
Odour threshold	data not available
pH	data not available
Melting point/freezing point	data not available
Initial boiling point and boiling range	120 °C
Flash point	18 °C
Evaporation rate	data not available
Flammability (solid, gas)	Highly flammable liquid and vapour.
Upper/lower flammability or explosive limits	
flammability limits	data not available
explosive limits	data not available
Vapour pressure	data not available
Vapour density	data not available
Relative density	data not available
Solubility(ies)	
solubility in water	insoluble
solubility in fats	data not available
Partition coefficient: n-octanol/water	data not available
Auto-ignition temperature	data not available
Decomposition temperature	data not available
Viscosity	data not available
Explosive properties	data not available
Oxidising properties	data not available

9.2. Other information

Density	0,934 g/cm ³
ignition temperature	data not available

SECTION 10: Stability and reactivity

10.1. Reactivity

not available

10.2. Chemical stability

The product is stable under normal conditions.

10.3. Possibility of hazardous reactions

Unknown.

10.4. Conditions to avoid

The product is stable and no degradation occurs under normal use. Protect against flames, sparks, overheating and against frost.

10.5. Incompatible materials

Protect against strong acids, bases and oxidizing agents.

10.6. Hazardous decomposition products

Not developed under normal uses. Dangerous outcomes such as carbon monoxide and carbon dioxide are formed at high temperature and in fire.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

No toxicological data is available for the mixture.

SAFETY DATA SHEET

according to Regulation (EC) No 1907/2006 (REACH) as amended



Sample Logo

EXAMPLE Dangerous mixture

Creation date

10th December 2019

Revision date

Version

1.0

Acute toxicity

Based on available data the classification criteria are not met.

ALCOHOL

Route of exposure	Parameter	Method	Value	Time of exposure	Species	Sex
Inhalation (vapor)	LC ₅₀		124.7 mg/l	4 hour	Rat	
Oral	LD Lo		7000 mg/kg bw		Rat	
Inhalation (vapor)	LC ₅₀		116.9 mg/l	4 hour	Rat	
Inhalation (vapor)	LC ₅₀		133.8 mg/l	4 hour	Rat	

cyclohexane

Route of exposure	Parameter	Method	Value	Time of exposure	Species	Sex
Dermal	LD ₅₀		>2000 mg/kg		Rat	
Oral	LD ₅₀		>5000 mg/kg bw/day		Rat	F/M

ethylbenzene

Route of exposure	Parameter	Method	Value	Time of exposure	Species	Sex
Oral	LD ₅₀		3500 mg/kg		Rat	
Dermal	LD ₅₀		17800 mg/kg		Rat	
Dermal	LD ₅₀		15433 mg/kg		Rabbit	
Inhalation (vapor)	LC ₅₀		17.4 mg/l	4 hour	Rat	
Oral	LD ₅₀		4769 mg/kg		Rat	
Inhalation (vapor)	LC ₅₀		17400 mg/kg	4 hour	Rat	

isopropanol

Route of exposure	Parameter	Method	Value	Time of exposure	Species	Sex
Oral	LD ₅₀		5.84 mg/kg		Rat	
Inhalation (vapor)	LC ₅₀	OECD 403	>10000 ppm	6 hour	Rat	F/M

Skin corrosion/irritation

Causes skin irritation.

ethylbenzene

Route of exposure	Result	Time of exposure	Species
	Slightly irritating		Rabbit

Serious eye damage/irritation

Causes serious eye irritation.

ALCOHOL

Route of exposure	Result	Method	Time of exposure	Species
	Irritating			Rabbit

cyclohexane

Route of exposure	Result	Method	Time of exposure	Species
	Slightly irritating			Rabbit

ethylbenzene

Route of exposure	Result	Method	Time of exposure	Species
	Irritating			Rabbit

SAFETY DATA SHEET

according to Regulation (EC) No 1907/2006 (REACH) as amended



Sample Logo

EXAMPLE Dangerous mixture

Creation date 10th December 2019
Revision date Version 1.0

isopropanol

Route of exposure	Result	Method	Time of exposure	Species
Eye	Serious eye damage	OECD 405		Rabbit

Respiratory or skin sensitisation

May cause an allergic skin reaction.

cyclohexane

Route of exposure	Result	Time of exposure	Species	Sex
	Not sensitizing			

ethylbenzene

Route of exposure	Result	Time of exposure	Species	Sex
	Not sensitizing		Human	

isopropanol

Route of exposure	Result	Time of exposure	Species	Sex
	Not sensitizing		Guinea-pig	F/M

Mutagenicity

isopropanol

Result	Time of exposure	Specific target organ	Species	Sex
Negative without metabolic regeneration, Negative with metabolic regeneration		Ovary	Guinea-pig	F/M

Germ cell mutagenicity

Based on available data the classification criteria are not met.

Carcinogenicity

Based on available data the classification criteria are not met.

ALCOHOL

Route of exposure	Parameter	Value	Result	Species	Sex
Oral			Indeterminate	Rat	

Reproductive toxicity

Based on available data the classification criteria are not met.

ALCOHOL

	Parameter	Value	Result	Species	Sex
Effects on fertility	NOAEL	>16000 ppm	No effect	Rat	
	NOAEL	5200 mg/kg/24hour	Indeterminate	Rat	

ethylbenzene

	Parameter	Value	Result	Species	Sex
	NOAEL	4.3 mg/l	Indeterminate	Rat	

SAFETY DATA SHEET

according to Regulation (EC) No 1907/2006 (REACH) as amended



Sample Logo

EXAMPLE Dangerous mixture

Creation date	10th December 2019	Version	1.0
Revision date			

Toxicity for specific target organ - single exposure

May cause drowsiness or dizziness.

ALCOHOL

Route of exposure	Parameter	Value	Time of exposure	Specific target organ	Result	Species	Sex
Inhalation	LOAEL	2.6 mg/l	30 min	Nervous system	Drowsiness, Dizziness	Human	
Inhalation	LOAEL	9.4 mg/l		Lungs	Indeterminate	Human	

ethylbenzene

Route of exposure	Parameter	Value	Time of exposure	Specific target organ	Result	Species	Sex
Inhalation	NOAEL			Nervous system	Drowsiness, Dizziness	Human	

Toxicity for specific target organ - repeated exposure

May cause damage to hearing organs, the kidneys through prolonged or repeated exposure.

cyclohexane

Route of exposure	Parameter	Value	Time of exposure	Specific target organ	Result	Species	Sex
Inhalation	NOAEC	500 mg/l				Mouse	
Inhalation	NOAEC	2000 ppm				Mouse	

ethylbenzene

Route of exposure	Parameter	Value	Time of exposure	Specific target organ	Result	Species	Sex
Inhalation	NOAEL	1.1 mg/l		Kidney	Indeterminate	Rat	
Inhalation	NOAEL	1.1 mg/l	103 week	Liver	Indeterminate	Mouse	
Inhalation	NOAEL	3.4 mg/l	28 day	Bone marrow	Indeterminate	Rat	
Inhalation	NOAEL	2.4 mg/l	5 day		Indeterminate	Rat	
Inhalation	NOAEL	3.3 mg/l	103 week	Endocrine system	Indeterminate	Mouse	

isopropanol

Route of exposure	Parameter	Value	Time of exposure	Specific target organ	Result	Species	Sex
Inhalation (vapor)	NOEC	500 ppm				Rat (Rattus norvegicus)	F/M

Aspiration hazard

May be fatal if swallowed and enters airways.

SECTION 12: Ecological information

12.1. Toxicity

Acute toxicity

Toxic to aquatic life with long lasting effects.

ALCOHOL

Parameter	Value	Time of exposure	Species	Environment	Determining method
EC 0	3.9 g/l	200 hour	Fishes		Experimentally
EC ₅₀	>10000 mg/l	48 hour	Daphnia		Experimentally
IC ₅₀	8800 mg/l	96 hour	Algae		Experimentally

SAFETY DATA SHEET

according to Regulation (EC) No 1907/2006 (REACH) as amended



Sample Logo

EXAMPLE Dangerous mixture

Creation date

10th December 2019

Version

1.0

Revision date

cyclohexane

Parameter	Value	Time of exposure	Species	Environment	Determining method
EC ₅₀	3.78 mg/l	48 hour	Daphnia (Daphnia magna)		
EC ₅₀	3.4 mg/l	72 hour	Algae		
IC ₅₀	0.9 mg/l	72 hour	Algae		
LC ₅₀	9.317 mg/l	96 hour	Fishes (Oncorhynchus mykiss)		

ethylbenzene

Parameter	Value	Time of exposure	Species	Environment	Determining method
EC ₅₀	1.81 mg/l	48 hour	Daphnia		Experimentally
IC ₅₀	3.6 mg/l	72 hour	Algae		Experimentally
LC ₅₀	4.2 mg/l	96 hour	Fishes		Experimentally

isopropanol

Parameter	Value	Time of exposure	Species	Environment	Determining method
EC ₅₀	>10000 mg/l	48 hour	Daphnia (Daphnia magna)		
LC ₅₀	9640 mg/l	96 hour	Fishes	Freshwater	

Chronic toxicity

ALCOHOL

Parameter	Value	Time of exposure	Species	Environment	Determining method
LC ₅₀	9248 mg/l	48 hour	Invertebrates		Experimentally
NOEC	250 mg/l	120 hour	Fishes (Oncorhynchus mykiss)		Experimentally
NOEC	1000 mg/l	120 hour	Fishes		Experimentally

cyclohexane

Parameter	Value	Time of exposure	Species	Environment	Determining method
NOEC	0.94 mg/l	72 hour	Algae		

12.2. Persistence and degradability

Data not available.

12.3. Bioaccumulative potential

Not available.

12.4. Mobility in soil

Not available.

12.5. Results of PBT and vPvB assessment

Product does not contain any substance meeting the criteria for PBT or vPvB in accordance with the Annex XIII of Regulation (EC) No 1907/2006 (REACH) as amended.

12.6. Other adverse effects

Not available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Hazard of environmental contamination; dispose of the waste in accordance with the local and/or national regulations. Proceed in accordance with valid regulations on waste disposal. Any unused product and contaminated packaging should be put in labelled containers for waste collection and submitted for disposal to a person authorised for waste removal (a specialized company) that is entitled for such activity. Do not empty unused product in drainage systems. The product must not be disposed of with municipal waste. Empty containers may be used at waste incinerators to produce energy or deposited in a dump with appropriate classification. Perfectly cleaned containers can be submitted for recycling.

SAFETY DATA SHEET

according to Regulation (EC) No 1907/2006 (REACH) as amended



Sample Logo

EXAMPLE Dangerous mixture

Creation date 10th December 2019
Revision date Version 1.0

Waste management legislation

Directive 2008/98/EC of the European Parliament and of the Council of 19 November 2008 on waste, as amended. Decision 2000/532/EC establishing a list of wastes, as amended.

Waste type code

14 06 03 other solvents and solvent mixtures *

Packaging waste type code

15 01 02 plastic packaging

(*) - Hazardous waste according to Directive 2008/98/EC on hazardous waste

SECTION 14: Transport information

14.1. UN number

UN 1993

14.2. UN proper shipping name

FLAMMABLE LIQUID, N.O.S. (ethylbenzene)

14.3. Transport hazard class(es)

3 Flammable liquids

14.4. Packing group

I - substances presenting high danger

14.5. Environmental hazards

not available

14.6. Special precautions for user

Reference in the Sections 4 to 8.

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

not available

Additional information

Hazard identification No.

33

(Kemler Code)

UN number

1993

Classification code

F1

Safety signs

3+hazardous for the environment



Air transport - ICAO/IATA

Packaging instructions passenger

351

Cargo packaging instructions

361

Marine transport - IMDG

EmS (emergency plan)

F-E, S-E

MFAG

310

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Regulation (EC) No. 1907/2006 of the European Parliament and of the Council of 18th December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing the European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No. 793/93 and Commission Regulation (EC) No. 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC, as amended. Regulation (EC) No. 1272/2008 of the European Parliament and of the Council of 16th December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No. 1907/2006, as amended.

SAFETY DATA SHEET

according to Regulation (EC) No 1907/2006 (REACH) as amended



Sample Logo

EXAMPLE Dangerous mixture

Creation date 10th December 2019
Revision date Version 1.0

Restrictions pursuant to Annex XVII of Regulation (EC) No. 1907/2006 (REACH), as amended

cyclohexane

Restriction	Conditions of restriction
57	<p>1. Shall not be placed on the market for the first time after 27 June 2010, for supply to the general public, as a constituent of neoprene-based contact adhesives in concentrations equal to or greater than 0,1 % by weight in package sizes greater than 350 g.</p> <p>2. Neoprene-based contact adhesives containing cyclohexane and not conforming to paragraph 1 shall not be placed on the market for supply to the general public after 27 December 2010.</p> <p>3. Without prejudice to other Community legislation concerning the classification, packaging and labelling of substances and mixtures, suppliers shall ensure before the placing on the market that neoprene-based contact adhesives containing cyclohexane in concentrations equal to or greater than 0,1 % by weight that are placed on the market for supply to the general public after 27 December 2010 are visibly, legibly and indelibly marked as follows:</p> <p>— This product is not to be used under conditions of poor ventilation. — This product is not to be used for carpet laying.”</p>

15.2. Chemical safety assessment

not available

SECTION 16: Other information

A list of standard risk phrases used in the safety data sheet

H225	Highly flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H336	May cause drowsiness or dizziness.
H373	May cause damage to hearing organs through prolonged or repeated exposure.
H373	May cause damage to the kidneys through prolonged or repeated exposure.
H373	May cause damage to hearing organs, the kidneys through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.

Guidelines for safe handling used in the safety data sheet

P301+P310	IF SWALLOWED: Immediately call a doctor.
P331	Do NOT induce vomiting.
P391	Collect spillage.
P280	Wear protective gloves.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P370+P378	In case of fire: Use powder extinguisher/sand/carbon dioxide to extinguish.

Other important information about human health protection

The product must not be - unless specifically approved by the manufacturer/importer - used for purposes other than as per the Section 1. The user is responsible for adherence to all related health protection regulations.

Key to abbreviations and acronyms used in the safety data sheet

ADR	European agreement concerning the international carriage of dangerous goods by road
BCF	Bioconcentration Factor
CAS	Chemical Abstracts Service
CLP	Regulation (EC) No 1272/2008 on classification, labelling and packaging of substance and mixtures
DNEL	Derived no-effect level
EC	Identification code for each substance listed in EINECS
EC ₅₀	Concentration of a substance when it is affected 50% of the population
EINECS	European Inventory of Existing Commercial Chemical Substances
EmS	Emergency plan

SAFETY DATA SHEET

according to Regulation (EC) No 1907/2006 (REACH) as amended



Sample Logo

EXAMPLE Dangerous mixture

Creation date	10th December 2019	Version	1.0
Revision date			

EU	European Union
IATA	International Air Transport Association
IBC	International Code For The Construction And Equipment of Ships Carrying Dangerous Chemicals
IC ₅₀	Concentration causing 50% blockade
ICAO	International Civil Aviation Organization
IMDG	International Maritime Dangerous Goods
INCI	International Nomenclature of Cosmetic Ingredients
ISO	International Organization for Standardization
IUPAC	International Union of Pure and Applied Chemistry
LC ₅₀	Lethal concentration of a substance in which it can be expected death of 50% of the population
LD ₅₀	Lethal dose of a substance in which it can be expected death of 50% of the population
LOAEC	Lowest observed adverse effect concentration
LOAEL	Lowest observed adverse effect level
log K _{ow}	Octanol-water partition coefficient
MARPOL	International Convention for the Prevention of Pollution From Ships
NOAEC	No observed adverse effect concentration
NOAEL	No observed adverse effect level
NOEC	No observed effect concentration
NOEL	No observed effect level
OEL	Occupational Exposure Limits
PBT	Persistent, Bioaccumulative and Toxic
PNEC	Predicted no-effect concentration
ppm	Parts per million
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals
RID	Agreement on the transport of dangerous goods by rail
UN	Four-figure identification number of the substance or article taken from the UN Model Regulations
UVCB	Substances of unknown or variable composition, complex reaction products or biological materials
VOC	Volatile organic compounds
vPvB	Very Persistent and very Bioaccumulative
Acute Tox.	Acute toxicity
Aquatic Acute	Hazardous to the aquatic environment
Aquatic Chronic	Hazardous to the aquatic environment
Asp. Tox.	Aspiration hazard
Eye Irrit.	Eye irritation
Flam. Liq.	Flammable liquid
Skin Irrit.	Skin irritation
Skin Sens.	Skin sensitization
STOT RE	Specific target organ toxicity - repeated exposure
STOT SE	Specific target organ toxicity - single exposure

Training guidelines

Inform the personnel about the recommended ways of use, mandatory protective equipment, first aid and prohibited ways of handling the product.

Recommended restrictions of use

not available

Information about data sources used to compile the Safety Data Sheet

REGULATION (EC) No. 1907/2006 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL (REACH) as amended.
REGULATION (EC) No. 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL as amended. Data from the manufacturer of the substance / mixture, if available - information from registration dossiers.

More information

Classification procedure - calculation method.

Statement

SAFETY DATA SHEET

according to Regulation (EC) No 1907/2006 (REACH) as amended



Sample Logo

EXAMPLE Dangerous mixture

Creation date	10th December 2019	Version	1.0
Revision date			

The safety data sheet provides information aimed at ensuring safety and health protection at work and environmental protection. The provided information corresponds to the current status of knowledge and experience and complies with valid legal regulations. The information should not be understood as guaranteeing the suitability and usability of the product for a particular application.